

---

## 1. PRODUCT AND COMPANY IDENTIFICATION

---

MSDS data revised 27 Jan. 2011

Product Code	
Trade Name	CONFIAD JOINT ADHESIVE COMPONENT B
Product Type	Preparation
Manufacturer/Supplier	Jin Gwang Industry Co., Ltd
Address	232-8 Maesan-ri Opo-eup, Gwangju-si, Gyeonggi-do, Korea
Phone Number	82-31-767-8441
Fax Number	82-31-767-8442

---

## 2. COMPOSITION / INFORMATION ON THE COMPONENTS

---

Benzoyl Peroxide	3~7%	CAS Number	: 94-36-0
Material	93~97%	This information should be kept secret for sales.	

---

## 3. HAZARD IDENTIFICATION

---

Main Hazards	Harmful if swallowed. Risks of serious damage to eyes.
Health Effects-Eyes	Liquid or mist will cause severe conjunctiva irritation and corneal damage.
Health Effects-Skin	Material may cause irritation. repeated or prolonged contact may produce defatting of the skin leading to irritation and dermatitis.
Health Effects-Ingestion	Swallowing may have the following effects: irritation of mouth, throat and digestive tract. nausea. difficulty with breathing. lung damage.
Health Effects-Inhalation	Low volatility makes acute effects unlikely at ambient temperatures.

---

## 4. FIRST AID MEASURES

---

First Aid-Eyes	Immediately flood the eye with plenty of water for at least 15 minutes. holding the eye open. Obtain medical attention urgently.
First Aid-Skin	Wash skin thoroughly with soap and water. Contaminated clothing should be washed or dry-cleaned before re-use.
First Aid-Ingestion	Wash out mouth with water. (Never administer anything by mouth if a casualty is losing consciousness, is unconscious or is convulsing). do not induce vomiting. Keep warm and at rest. If there is difficulty in breathing, give oxygen. If breathing stops or shows signs of failing, apply artificial respiration. Do not use mouth to mouth ventilation. Obtain medical attention urgently.
First Aid-Inhalation	Remove from exposure. Keep warm and at rest. If there is difficulty in breathing, give oxygen. If breathing stops or shows signs of failing, give artificial respiration.
Advice to Physicians	Obtain medical attention. Treat symptomatically.

---

## 5. FIRE FIGHTING MEASURES

---

Extinguishing Media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Keep containers and surroundings cool with water spray.
Unsuitable Media	Do not use water jet.
Special Hazards	This product may give rise to hazardous fumes in a fire.
Protective Equipment	Wear self contained breathing apparatus.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

Personal Precautions	Wear appropriate protective clothing. Wear respiratory protection.
Environmental Precautions	Try to prevent the material from entering drains or water courses. Advise Authorities if spillage has entered water course or sewer or has contaminated soil or vegetation.
Spillages	Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal.

---

## 7. HANDLING AND STORAGE

---

Handling	Keep container tightly closed when not in use. Use in well ventilated area. Avoid inhaling vapour. Avoid contact with eyes, skin and clothing. Emergency shower and eye wash facilities should be readily available.
Storage	Storage area should be : cool, dry, well ventilated.

---

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

---

Occupational Exposure	Material may cause irritation to mucous membranes, skin burns, eye corrosion and permanent injury. ( TLV : 100 ppm )
Engineering Control Measures	Engineering methods to prevent or control exposure are preferred. Methods include process or personnel enclosure, mechanical ventilation (dilution and local exhaust), and control of process conditions. If engineering controls and work practices are not effective in preventing or controlling exposure, then suitable personal protective equipment, which is known to perform satisfactorily, should be used.
Respiratory Protection	Respiratory protection if there is risk of breathing mists or vapors from heated material.
Hand Protection	Rubber or polyethylene gloves.
Eye Protection	Chemical goggles must be worn during all handling operations.
Body Protection	If there is danger of splashing, wear impermeable suit.
Ventilation	During application, adequate ventilation must be provided.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

Physical State	Viscous liquid.
Color	Transparent
Odor	Mild
Flash Point (TOC)	100°C
Ignition Temperature	No data available.
Explosion Limits	No data available.
Solubility in Water	Insoluble
Specific gravity	1.1

---

## 10. STABILITY AND REACTIVITY

---

Stability	Stable under normal condition.
Condition to avoid	Heat, spark, flames and other sources of ignition.
Materials to avoid	Amine, Strong acid.
Hazardous Polymerization	Combustion will generate : oxides of carbon, smoke.

---

## 11. TOXICOLOGICAL INFORMATION

---

Acute Toxicity	Harmful by ingestion.
Carcinogenicity	NTP : None assigned JARC : None assigned OSHA : None assigned
Contact Hazard	Moderate

---

## 12. ECOLOGICAL INFORMATION

---

Mobility	The product will not dissolve in water.
Persistence/Degradability	The product is expected to be partially or slowly biodegradable.
Bio-accumulation	The product is not expected to bioaccumulate.
Ecotoxicity	No data

---

## 13. DISPOSAL

---

Product Disposal	Dispose of in accordance with all applicable local and national regulations. Incineration is the recommended method of disposal. Empty containers may contain hazardous residues. Labels should not be removed from containers until they have been cleaned. Contaminated containers must not be treated as household waste. Containers should be disposed of by landfill or incineration as appropriate.
Container Disposal	

---

## 14. TRANSPORT INFORMATION

---

\*\*\* This information relates to the kit as a whole ( Component A, Component B ).

ADR / RID – Class	UN-NO 1133	Class 3	Item 5(C)
	Proper shipping name : Adhesives		
	Term-Card R-30G80	ADR/RID Labels : 3	
ICAO – Class	UN-NO 1133	Class 3	Subrisks
	Proper shipping name : Adhesives		
	Packing Group II	ICAO Labels : Flammable liquid	

---

## 15. REGULATORY INFORMATION

---

Labeling Information	Warning : Flammable, Irritant. Contents : Benzoyl Peroxide Common name : CONFIAD ADHESIVE COMPONENT B
Caution	Always wear safety goggles and protective gloves. Keep away from children. CONFIAD ADHESIVE should be stored in a cool and dark area. Avoid breathing vapor and use only with adequate ventilation. Keep away from heat, sparks, open flame and other combustible materials. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

---

## 16. OTHER INFORMATION

---

MSDS first issued	17 December 2001
MSDS data revised	27 Jan. 2011
Revision Highlighted	Basic form

We hereby certify that the above statements are true and correct in every respect.  
If the statements are not true, all responsibility will belong to Jin Gwang Industry Co.,Ltd.

Signature / Issued Date :



---

President / Jahng Nyul Kim

Jin Gwang Industry Co.,Ltd.



***MATERIAL SAFETY DATA SHEET***

Jin Gwang Industry Co.,Ltd